

BS ISO 5073:2013



BSI Standards Publication

Brown coals and lignites — Determination of humic acids

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

raising standards worldwide™



National foreword

This British Standard is the UK implementation of ISO 5073:2013.

The UK participation in its preparation was entrusted to Technical Committee PTI/16, Solid mineral fuels.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2013. Published by BSI Standards Limited 2013

ISBN 978 0 580 81215 6

ICS 73.040

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 May 2013.

Amendments issued since publication

Date	Text affected
------	---------------

INTERNATIONAL STANDARD

BS ISO 5073:2013

ISO
5073

Third edition
2013-05-01

Brown coals and lignites — Determination of humic acids

Charbons bruns et lignites — Dosage des acides humiques



Reference number
ISO 5073:2013(E)

© ISO 2013



COPYRIGHT PROTECTED DOCUMENT

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	1
4.1 Total humic acids.....	1
4.2 Free humic acid.....	2
5 Reagents	2
6 Apparatus	3
7 Sample	3
8 Procedure	3
8.1 Extraction of total humic acids.....	3
8.2 Extraction of free humic acid.....	3
8.3 Determination of humic acids in extracts.....	3
9 Expression of results	4
10 Precision of the method — Repeatability limit	4
11 Test report	5
Annex A (normative) Determination of the ratio of carbon content of humic acids of brown coals and lignites	6

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 5073 was prepared by Technical Committee ISO/TC 27, *Solid mineral fuels*, Subcommittee SC 5, *Methods of analysis*.

This third edition cancels and replaces the second edition (ISO 5073:1999), of which this constitutes a minor revision.

Introduction

In this International Standard, humic acids are determined by the volumetric method with titration of extracts.

The test is empirical and, in order to ensure producible results, it is essential that the composition of the extraction solution, the temperature and the time of extraction be carefully controlled. The value 0,59, which is the average ratio of carbon content of humic acids for many brown coals and lignites, has been proved to be applicable. Another value may also be used, predetermined as described in [Annex A](#), and applicable to different countries or locations.

Brown coals and lignites — Determination of humic acids

1 Scope

This International Standard specifies volumetric methods for the determination of

a) total humic acids, and

b) free humic acid,

of brown coals and lignites.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1171, *Solid mineral fuels — Determination of ash*

ISO 1213-2, *Solid mineral fuels — Vocabulary — Part 2: Terms relating to sampling, testing and analysis*

ISO 5068-2, *Brown coals and lignites — Determination of moisture content — Part 2: Indirect gravimetric method for moisture in the analysis sample*

ISO 5069-2, *Brown coals and lignites — Principles of sampling — Part 2: Sample preparation for determination of moisture content and for general analysis*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 1213-2 and the following apply.

3.1

humic acids

group of complex organic, amorphous compounds of high relative molecular mass which occur as free acid and as metal salts (humates)

3.2

total humic acids

humic acids extracted by an alkaline sodium pyrophosphate solution

3.3

free humic acid

humic acid extracted by a sodium hydroxide solution

4 Principle

4.1 Total humic acids

Extraction of an analysis sample of coal is carried out with an alkaline sodium pyrophosphate solution. Carbon in the humic acid extracts is oxidized with potassium dichromate followed by titration of the excess dichromate with ammonium ferrous sulfate standard solution.

4.2 Free humic acid

Extraction of an analysis sample of coal is carried out with a sodium hydroxide solution. Carbon in the humic acid extracts is oxidized with potassium dichromate followed by titration of the excess dichromate with ammonium ferrous sulfate standard solution.

5 Reagents

5.1 Sodium pyrophosphate, alkaline extraction solution.

Dissolve 15 g of crystalline sodium pyrophosphate ($\text{Na}_4\text{P}_2\text{O}_7 \cdot 10\text{H}_2\text{O}$) and 7 g of sodium hydroxide in 1 l of water.

5.2 Sodium hydroxide solution.

Dissolve 10 g of sodium hydroxide in 1 l of water.

5.3 Potassium dichromate standard solution, $c(1/6 \text{K}_2\text{Cr}_2\text{O}_7) = 0,1 \text{ mol/l}$.

Dissolve 4,903 6 g of potassium dichromate, previously dried at 130 °C, in water. Transfer to a 1 l volumetric flask and dilute to the mark with water.

5.4 Potassium dichromate oxidizing solution, $c(1/6 \text{K}_2\text{Cr}_2\text{O}_7) = 0,4 \text{ mol/l}$.

Dissolve 20 g of potassium dichromate in 1 l of water.

5.5 Ammonium ferrous sulfate titration solution, $c[(\text{NH}_4)_2\text{Fe}(\text{SO}_4)_2] = 0,1 \text{ mol/l}$.

Dissolve 40 g of ammonium ferrous sulfate in 1 l of water. Add 20 ml of concentrated sulfuric acid. Store in a dark bottle.

Standardize the ammonium ferrous sulfate titration solution against the $c(1/6 \text{K}_2\text{Cr}_2\text{O}_7) = 0,1 \text{ mol/l}$ potassium dichromate standard solution (5.3) for each batch of samples to be analysed.

Pipette 25 ml of potassium dichromate standard solution (5.3) into a 300 ml conical flask. Add 70 ml to 80 ml of water. Carefully add 10 ml of concentrated sulfuric acid and 3 drops of 1,10-phenanthroline indicator. After cooling, titrate with the ammonium ferrous sulfate standard solution to a red colour.

Calculate the concentration, in moles per litre, of the ammonium ferrous sulfate solution as follows:

$$c = 0,1 \times 25/V$$

where

c is the concentration, expressed in moles per litre, of the ammonium ferrous sulfate solution;

V is the volume of ammonium ferrous sulfate solution required for the titration.

5.6 1,10-Phenanthroline indicator.

Dissolve 1,5 g of 1,10-phenanthroline and 1 g of ammonium ferrous sulfate in 100 ml of water. Store in a dark bottle.

5.7 Sulfuric acid, concentrated, $\rho_{20} = 1,84 \text{ g/ml}$.

6 Apparatus

6.1 Water bath, thermostatically controlled to $(100 \pm 1) ^\circ\text{C}$, with four holes at least.

6.2 Balance, sensitive to 0,1 mg.

7 Sample

Prepare the sample for the determination of humic acids in accordance with ISO 5069-2.

For calculation to a dry basis, the moisture in the analysis sample shall be determined according to ISO 5068-2.

8 Procedure

8.1 Extraction of total humic acids

Weigh $(0,2 \pm 0,000 2)$ g of analysis sample into a conical flask. Add 150 ml of alkaline sodium pyrophosphate extraction solution (5.1) and mix until the sample is thoroughly wetted. Place a small funnel on the flask and heat in the boiling water bath (6.1) for 2 h, shaking frequently to ensure precipitation of insoluble material.

Remove the flask from the water bath. Allow to cool to room temperature and quantitatively transfer the extract and residue to a 200 ml volumetric flask. Dilute to the mark with water and shake to ensure thorough mixing.

Determine the total humic acids ($w_{\text{HA,t}}$) extracted by alkaline sodium pyrophosphate as specified in 8.3.

8.2 Extraction of free humic acid

Weigh $(0,2 \pm 0,000 2)$ g of analysis sample into a conical flask. Add 150 ml of sodium hydroxide extraction solution (5.2) and mix until the sample is thoroughly wetted. Place a small funnel on the flask and heat in the boiling water bath (6.1) for 2 h, shaking frequently to ensure thorough mixing.

Remove the flask from the water bath. Allow to cool to room temperature and quantitatively transfer the extract and residue to a 200 ml volumetric flask using water. Dilute to the mark with water and shake to ensure thorough mixing.

Determine the free humic acid ($w_{\text{HA,f}}$) extracted by sodium hydroxide as specified in 8.3.

8.3 Determination of humic acids in extracts

8.3.1 Oxidation of extracts

Pipette 5 ml of clarified or dry-filtered extract into a 250 ml to 300 ml conical flask. Pipette 5 ml of potassium dichromate oxidizing solution (5.4) into the flask. Carefully add 15 ml of concentrated sulfuric acid (5.7). Place in the boiling water bath (6.1) and heat for 30 min. Allow to cool to room temperature. Dilute to approximately 100 ml.

8.3.2 Titration of extracts

Add 3 drops of 1,10-phenanthroline indicator (5.6) to the solution from 8.3.1 and titrate with the ammonium ferrous sulfate titration solution (5.5) to a brick red colour.

8.3.3 Blank

8.3.3.1 Blank for total humic acids

Pipette 5 ml of sodium pyrophosphate (5.1) into a 250 ml to 300 ml conical flask, add the potassium dichromate oxidizing solution (5.4) and the concentrated sulfuric acid as specified in 8.3.1 and carry out the titration as specified in 8.3.2.

8.3.3.2 Blank for free humic acids

Pipette 5 ml of sodium hydroxide (5.2) into a 250 ml to 300 ml conical flask, add the potassium dichromate oxidizing solution and the concentrated sulfuric acid as specified in 8.3.1 and carry out the titration as specified in 8.3.2.

9 Expression of results

Calculate the total humic acid content ($w_{\text{HA,t}}$) or free humic acid content ($w_{\text{HA,f}}$), as a percentage by mass, of the sample as analysed according to the following formula:

$$w_{\text{HA}} = \frac{(V_0 - V_1) \times 0,003 \times c}{0,59 \times m} \times \frac{V_e}{V_a} \times 100$$

where

- 0,003 is the millimole mass of carbon, in grams per millimole;
- V_0 is the volume of the ammonium ferrous sulfate titration solution used in the blank titre, in millilitres;
- V_1 is the volume of the ammonium ferrous sulfate titration solution used in the extract titre, in millilitres;
- c is the concentration of the ammonium ferrous sulfate titration solution as determined in 5.5, in moles per litre;
- V_e is the volume of the extract, in millilitres;
- V_a is the volume of the aliquot taken for titration, in millilitres;
- 0,59 is the average ratio of carbon content of humic acids for brown coals and lignites (see the note below);
- m is the mass of the sample taken for the test, in grams.

NOTE For different countries or locations, the average ratio of carbon content of humic acids of brown coals and lignites can be checked or redetermined as specified in [Annex A](#).

10 Precision of the method — Repeatability limit

The results of duplicate determinations, carried out on the same day in the same laboratory by the same operator with the same apparatus on the two separate test portions of the same sample, should not differ by more than the values given in Table 1.

Table 1 — Precision

Humic acid content	Repeatability limit
Up to 20 %	1 % (absolute)
Above 20 %	2 % (absolute)

11 Test report

The test report shall contain the following information:

- a) a reference to this International Standard including year of publication;
- b) the identification of the sample tested;
- c) the result of the determination performed, together with the analysis basis;
- d) any unusual feature noted during the determination.

Annex A (normative)

Determination of the ratio of carbon content of humic acids of brown coals and lignites

A.1 Weigh about 10 g of analysis sample of brown coals and lignites into three or four conical flasks separately depending on the humic acid content of the sample (can yield 3 g or 4 g of humic acid sample). Pipette an appropriate amount of the alkaline sodium pyrophosphate extraction (5.1) into each conical flask equivalent to 150 ml per gram of the analysis sample and mix until the sample is thoroughly wetted. Place a small funnel on the flask and heat in the boiling water bath (6.1) for 2 h, shaking frequently to ensure precipitation of insoluble material.

A.2 Remove the flask from the water bath, cool to room temperature, centrifuge the contents of flasks for 5 min. Collect the solution in the beakers. Add (1 + 1) HCl to the solution until the humic acid is precipitated fully (pH 1 to pH 3 for the solution).

A.3 Centrifuge the suspension. Decant and discard the solution. Separate the residue through a medium-textured paper, wash the residue with water until peptization of the humic acids begins, which is indicated by the formation of a gel or colloid (pH 6 to pH 7 for the filtered solution).

A.4 Transfer the residue to the clear beakers or vessels and dry it at 105 °C to 110 °C. The dried residue is the humic acid sample.

A.5 Weigh 1 g, to the nearest 0,2 mg, of the humic acid sample (A.4) into a clear, dry dish and determine the ash according to ISO 1171. Calculate the humic acid content (w_{HA}) of the humic acid sample as follows:

$$w_{\text{HA}} = 100 - w_{\text{A}}$$

where w_{A} is the ash of the humic acid sample, in percent.

A.6 Weigh 0,1 g, to the nearest 0,2 mg, of the humic acid sample (see A.4) into a conical flask. Add 150 ml of the alkaline sodium pyrophosphate extraction solution (5.1). Shake to enable it to be dissolved fully. Transfer the contents of the flask to a 200 ml volumetric flask and dilute to the mark with water. Shake to ensure thorough mixing, then dry-filter through a medium-textured paper into a flask. Accurately pipette 5 ml of filtered solution into a 250 ml conical flask. Determine the carbon content of the humic acid sample as specified in 8.3.

Calculate the carbon content (w_{C}) of the humic acid sample according to the formula:

$$w_{\text{C}} = \frac{(V_0 - V_1) \times 0,003 \times c}{m} \times \frac{V_{\text{e}}}{V_{\text{a}}} \times 100$$

where

0,003 is the millimole mass of carbon, in grams per millimole;

V_0 is the volume of the ammonium ferrous sulfate titration solution (5.5) used in the blank titre, in millilitres;

- V_1 is the volume of the ammonium ferrous sulfate titration solution (5.5) used in the extract titre, in millilitres;
- c is the concentration of the ammonium ferrous sulfate titration solution as determined in 5.5, in moles per litre;
- V_e is the volume of the extract, in millilitres;
- V_a is the volume of the aliquot taken for titration, in millilitres;
- m is the mass of the humic acid sample taken for the test, in grams.

A.7 The ratio of carbon content of humic acid is calculated as follows:

$$R_C = \frac{w_C}{w_{HA}}$$

where

- w_C is the carbon content of the humic acid sample, in percent (A.6);
- w_{HA} is the humic acid content of the humic acid sample, in percent (A.5).

ICS 73.040

Price based on 7 pages

British Standards Institution (BSI)

BSI is the independent national body responsible for preparing British Standards and other standards-related publications, information and services. It presents the UK view on standards in Europe and at the international level.

BSI is incorporated by Royal Charter. British Standards and other standardisation products are published by BSI Standards Limited.

Revisions

British Standards and PASs are periodically updated by amendment or revision. Users of British Standards and PASs should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using British Standards would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover. Similar for PASs, please notify BSI Customer Services.

Tel: +44 (0)20 8996 9001 Fax: +44 (0)20 8996 7001

BSI offers BSI Subscribing Members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of British Standards and PASs.

Tel: +44 (0)20 8996 7669 Fax: +44 (0)20 8996 7001
Email: plus@bsigroup.com

Buying standards

You may buy PDF and hard copy versions of standards directly using a credit card from the BSI Shop on the website www.bsigroup.com/shop. In addition all orders for BSI, international and foreign standards publications can be addressed to BSI Customer Services.

Tel: +44 (0)20 8996 9001 Fax: +44 (0)20 8996 7001
Email: orders@bsigroup.com

In response to orders for international standards, BSI will supply the British Standard implementation of the relevant international standard, unless otherwise requested.

Information on standards

BSI provides a wide range of information on national, European and international standards through its Knowledge Centre.

Tel: +44 (0)20 8996 7004 Fax: +44 (0)20 8996 7005
Email: knowledgecentre@bsigroup.com

BSI Subscribing Members are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration.

Tel: +44 (0)20 8996 7002 Fax: +44 (0)20 8996 7001
Email: membership@bsigroup.com

Information regarding online access to British Standards and PASs via British Standards Online can be found at www.bsigroup.com/BSOL

Further information about British Standards is available on the BSI website at www.bsi-group.com/standards

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that own copyright in the information used (such as the international standardisation bodies) has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained. Details and advice can be obtained from the Copyright & Licensing Department.

Tel: +44 (0)20 8996 7070
Email: copyright@bsigroup.com

BSI

389 Chiswick High Road London W4 4AL UK
 Tel +44 (0)20 8996 9001
 Fax +44 (0)20 8996 7001
www.bsigroup.com/standards